



3M™ IJ-35C

4mil Pressure Sensitive Adhesive Vinyl
3M Comply™ Air Release

Common Uses

Windows, Walls, Promotions, Retail, Event Graphics & More

Environment

Indoor & Outdoor

Print Sides

Single-sided

Size Options

Custom Size

Options

Contour Cut

Gloss, Matte or No Laminate

[Technical Data >](#)

TECHNICAL DATA SHEET

PROPERTIES

Pressure-sensitive adhesive with Comply™ Adhesive for fast, easy bubble-free installations

PHYSICAL CHARACTERISTICS

Material: Vinyl

Color: White opaque

Film thickness: Without adhesive: 3.2 mil (0.081 mm) With adhesive: 4.0 mil (0.102 mm)

Adhesive type: Pressure-sensitive

Adhesive color: Gray

Liner: Polycoated paper

APPLICATION CHARACTERISTICS

Finished graphic application recommendations

Surface type: Smooth, flat and simple curved surfaces

Substrate type: Metal, rigid plastic and painted substrates

Application temperature: air and substrate 40° to 100°F (4° to 38°C)

Application method: Dry

Finished graphic exposure temperature: -59° to +192°F (-50° to +90°C)

Graphic removal: Permanent

EXPOSURE TYPES

U.S. Vertical Exposure: The face of the graphic is +/- 10° from vertical.